



## General Staging Model SA155-2

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The loudspeaker shall be a two-way type with two 15" low/mid frequency drivers mounted in a bass reflex enclosure and one high frequency ClearFibertm horn flare utilizing a 2" throat compression driver. The low frequency section shall contain two 15" "Focused Field" drivers with a power handling capacity of 900 watts RMS and shall have a sensitivity of 101 dB SPL measured at 1 meter with 2.83 volts into a nominal 4 ohm load.

The high frequency section shall consist of one 2" exit compression driver and horn combination with a power handling capacity of 100 watts RMS and a sensitivity of 111 dB SPL measured at 1 meter with 2.83 volts into a nominal 16 ohm load. The combined loudspeaker system shall be capable of 132 dB SPL continuous and 138 dB SPL peak maximum output. The loudspeaker system shall have an effective operating range of 45 Hz to 12 kHz +/- 3 dB (40Hz to 18 kHz -10 dB). The loudspeaker shall offer coverage angles of 90o Horizontal, and 40o Vertical.

The enclosure shall weigh a total of 145 lbs. and shall measure 42 inches tall, 22 inches wide (13.5 inches at rear) and 24 inches in depth. The enclosure sides shall be angled at 10o from front to back forming a trapezoidal shape. The enclosure shall be made of 12-ply void-free birch hardwood and shall have a weather and wear resistant ProCoattm elastomeric finish. The enclosure shall incorporate two steel handles on each side and one on top, for easy mobility. Electrical connections shall be made via paralleled Neutrik NL-4 connectors, or optional NL-8 or EP series connectors. An optimized passive crossover network shall be switchable between full range and biamp modes.

The loudspeaker shall be the McCauley SA155-2.