



Installation Model AC95-1

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The loudspeaker shall be a two-way type with one 15" Full Range 2 Way Coaxial Point Source driver mounted in a bass reflex enclosure. The low frequency section shall contain one MCX 15" "Focused Field" driver with a power handling capacity of 400 watts RMS and shall have a sensitivity of 98 dB SPL measured at 1 meter with 2.83 volts into a nominal 8 ohm load.

The high frequency section shall consist of one MCX 1" exit compression driver and horn combination with a power handling capacity of 100 watts RMS and a sensitivity of 109 dB SPL measured at 1 meter with 2.83 volts into a nominal 16 ohm load. The combined loudspeaker system shall be capable of 125dB SPL continuous and 131 dB SPL peak maximum output. The loudspeaker system shall have an effective operating range of 60 Hz to 17 kHz +/- 3 dB (50Hz to 20 kHz -10 dB). The loudspeaker shall offer symmetrical coverage angles of 80o Horizontal, and 80o Vertical.

The enclosure shall weigh a total of 58 lbs. and shall measure 20 inches tall, 17.9 inches wide (10.5 inches at rear), 15.9 inches deep. Shall have a flat top and bottom, and the sides shall be angled at 15o from front to back forming a trapezoidal shape. The enclosure shall be made of 12-ply birch hardwood and shall have a weather and wear resistant ProCoat™ elastomeric finish. Electrical connections shall be made via standard binding posts or barrier strips. An optional passive crossover network shall be mounted internally.

The loudspeaker shall be the McCauley AC95-1.